



ENGINE OIL HDX

10W-40

Product Description:

Engine Oil HDX 10W-40 is a extra high performance universal semi synthetic engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

Engine Oil HDX 10W-40 is formulated with high refined solvent mineral and synthetic base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

ENGINE OIL HDX 10W-40 exceeds the following performance criteria:

Approved	Mack EO-N DTFR 15B110 (MB 228.3)	Volvo VDS-3	Renault RLD-2
Exceeds	API CI-4 ACEA E7 Caterpillar ECF-1a, ECF-2 MB 229.1H Cummins CES 20077/20078 Mack EO-M+	API SL ACEA A3/B4 Global DHD-1 MTU Type 2 Voith retarder B	DDC 93K215 Deutz DQC-III-10 JASO DH-1 MAN M 3275 Allison TES-439
Pending	MB 235.28		



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	869.2
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	98.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.5
Viscosity Index		ASTM D2270	151
Viscosity CCS @-25°C	cP	ASTM D2270	6450
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	11.6
Sulphated Ash	%Wt	ASTM D874	1.5

Product Nr: 42550

Date Superseded: 14-07-2022

Date Issued: 4-4-2025

Revision nr: 11