



MONO ENGINE OIL CF 10W

Product Description:

MONO ENGINE OIL CF 10W is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

MONO ENGINE OIL CF 10W is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

MONO ENGINE OIL CF 10W is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

MONO ENGINE OIL CF 10W exceeds the following performance criteria:

API CF-4

MB 228.0

Deutz DQC I-02

API SG

MB 228.1

ZF TE-ML 04A

ACEA E2

MAN 270

ZF TE-ML 04P

Volvo VDS

MAN 271

ZF TE-ML 07D



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W
Density@15°C	kg/m ³	ASTM D4052	884.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	40
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	6.4
Viscosity Index		ASTM D2270	110
Viscosity CCS @-25°C	cP	ASTM D5293	6490
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	11.8

Product Nr: 42620

Date Superseded: 30-06-2023

Date Issued: 4-4-2025

Revision nr: 08