



# AUTOGEAR OIL MP

## 75W-90

### Product Description:

**AUTOGEAR OIL MP 75W-90** is a universal high performance multi-purpose gear oil for use in differentials, axles and some transmissions of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 75W-90 GL-5 is been required.

**AUTOGEAR OIL MP 75W-90** is based on a high quality synthetic base oil in combination with a special additive package to ensure the following properties:

- Good extreme pressure and anti-wear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR OIL MP 75W-90** exceeds the following performance criteria:

API GL-5                      MIL-L-2105D                      MAN 342 M2                      Volvo STD 1273.1  
ZF TE-ML 05A, 7A, 16B, 17B, 21A



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	75W-90
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	869.0
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	97.6
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	15.0
Viscosity Index		ASTM D2270	162
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45

**Product Nr:** 43055

**Date Superseded:** 19-10-2022

**Date Issued:** 4-4-2025

**Revision nr:** 1