



ATF DX II

Product Description:

ATF DX II is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

ATF DX II is formulated on high quality re-refined mineral and virgin synthetic base oil in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against corrosion, foam and wear.

ATF DX II exceeds the following performance criteria:

GM Dexron II-D	Ford MERCON	Allison C3 & C4	CAT TO-2
Ford WSS M2C138CJ	Ford WSS M2C166H	Ford XT-2-QDX	Ford XT-2-QSM
Opel/GM 19 40 700	GM TASA	GM 1940700	Mazda ATF D-II
Volvo 97325	Volvo CE 97340	Toyota ATF D-II	Renault Matic D2
ZF TE-ML 03D/04D/05L/09/14A/17C/21L		Ford ESP-M2C166H, XL-12	



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m ³	ASTM D4052	845.5
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	34.0
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.1
Viscosity Index		ASTM D2270	180
Viscosity Brookfield @-40°	cP	ASTM D2983	18.000
Flash Point COC	°C	ASTM D92	180
Pour Point	°C	ASTM D7346	-48

Product Nr: 43200

Date Superseded: 10-03-2023

Date Issued: 4-4-2025

Revision nr: 07