



SUPER TRACTOR OIL 10W-40

Product Description:

SUPER TRACTOR OIL 10W-40 is a high quality universal synthetic so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).



SUPER TRACTOR OIL 10W-40 is formulated on synthetic base stocks in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

SUPER TRACTOR OIL 10W-40 exceeds the following performance criteria:

Engine Spec:	API CG-4/CF-4/CE/SF	MB 227.1	ACEA E3
UTTO/STOU Spec:	JD J20C, J20D, J27	Ford M2C86B, 134D	Ford M2C159B / C
	Case MS 1204, 6, 7, 9	MF M 1135/1139/1143/1144/1145	
	CAT TO-2	API GL-4	Allison C4
	ZF TE-ML 06A, 06B, 06C, 06D, 06E, 06H 07B		NH 82009201, 2, 3
Hydr. Spec:	Eaton M-2950S	Eaton I-280-S	Danfoss

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	10W-40
Density@15°C	kg/m ³	ASTM D4052	859.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	92.6
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	160
Viscosity CCS @-25°C,	cP	ASTM D5293	5200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	10.5

Product Nr: 43260
Date Superseded: 21-02-2023

Date Issued: 3-1-2025
Revision nr: 04