



UNIVERSAL TRACTOR OIL

85W

Product Description:

UNIVERSAL TRACTOR OIL 85W is a high performance fluids for use in transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors.

UNIVERSAL TRACTOR OIL 85W is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Enhanced frictional properties optimize clutch performance and ensure noise free operation of wet brakes.
- High viscosity index coupled with high shear stability provides consistent performance.
- Excellent low temperature fluidity provides good response and effective lubrication at low ambient temperatures.
- Robust anti-wear and extreme pressure properties control wear, extend equipment life and reduce maintenance costs.
- Multipurpose capability reduces inventory and prevents accidental contamination and misapplication.

UNIVERSAL TRACTOR OIL 85W exceeds the following performance criteria:

API GL-4	JD J20C	Ford M2C86B/C	Ford M2C 134D
Case MS 1204/6/7/9	MF M1135/1143	MF M1145	Cat TO-2
Volvo WB101	Allison C4	JCMAS HK P-041	Eaton M-2950S
Eaton I-280-S	Sauer Danfoss		



Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	85W
Density@15°C	kg/m ³	ASTM D4052	888.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	67.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.2
Viscosity Index		ASTM D2270	158
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	9.7

Product Nr: 43310

Date Superseded: 16-12-2019

Date Issued: 4-4-2025

Revision nr: 06