



ATF ULV Red

Product Description:

ATF ULV Red is a synthetic high quality ultra low viscosity automatic transmission fluid intended for 6-speed, 8-speed and 9-speed automatic car transmissions. Subjected to extreme testing.

ATF ULV Red guarantees maximum performance of the automatic transmission. At the same time, the wear of heavily loaded components is minimized due to the specifically matched oils.

ATF ULV Red is based on a synthetic base in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Excellent lubrication, even under extreme conditions.
- Very high protection against wear, corrosion and foam.
- High "shear stable".
- Very low Pour point, can be used by very cold temperatures.
- High Viscosity Index.

ATF ULV Red exceeds the performance criteria where the following specifications are asked:

Aisin-Warner AW-2
Volvo 31492172/312492173
MERCON ULV

PSA 16 350 560 80
BMW ATF 7
DEXRON ULV

VW G 053 001
VW G 053 001 A2

For a more detailed list, see the following pages.



Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density@15°C	kg/m ³	ASTM D4052	840.2
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	19.22
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	4.52
Viscosity Index		ASTM D2270	157
Flash Point COC	°C	ASTM D92	>180
Pour Point	°C	ASTM D7346	-42

Product Nr: 45016
Date Superseded: -

Date Issued: 24-11-2025
Revision nr: -



ATF ULV Red

ATF ULV Red is suitable for use where the following specifications are required:

Aisin Warner AW-2
Audi/VW G 055 005 -A, -A1, -A2, -A6 (ZF LifeguardFluid 6) (ZF No. S671 090 255)
Audi/VW G 055 162-A2, -A6 (ZF LifeguardFluid 6 Plus) (ZF No. S671 090 281)
Audi/VW G 060 162 (ZF LifeguardFluid 8) (ZF No. S671 090 312)
Audi/VW G 055 540 A2
Bentley PY112995PA
BMW ATF 2, ATF 3+, ATF 6, ATF 7
Chrysler/Dodge/Jeep 68043742AA, 68157995AA, 68157995AB
Chrysler/Dodge/Jeep 68218925AA and 68218925AB
FIAT 9.55550-AV5, 9.55550-AV6
Ford ATF C-ML5
Ford/Lincoln/Mercury XT-6-QSP or -DSP (SP)
GM/GMC/Opel/Saturn AW1
GM/GMC/Opel/Saturn VI
GM/GMC/Opel/Saturn 88863400 / 88863401
Honda Type 3.0, 3.1 : 08263-999-01HE (EU), 08200-9017 (USA) (ZF LifeguardFluid 9) (ZF No. AA01.500.001)
Honda Ultra HEVF-Type 1
Hyundai/Kia SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SPH-IV M1 (SP4-M1), SP-IV-RR
Hyundai/Kia NWS 9638
ISUZU ATF WSI
Jaguar Fluid 8432
Jaguar 02JDE26444
JASO M315-2015 1A-LV
Land Rover TYK500050, LR0022460
Maserati 231603
Mazda ATF FZ, ATF A7
Mitsubishi Diaqueen SP-IV, J3, MA-1, PA
Nissan Matic Fluid S, W
PSA 16 350 560 80
Saab 93 165 147
Saab Power Steering Fluid 2634, 45 30 09 800, 93160548
M-1375.4
Suzuki ATF AW-1
Toyota ATF WS
Volvo PN 31256774/31256675
VW G 055 540 (A2)
VW G 055 005-A, -A2 (ZF LifeguardFluid 6)
VW G 055 162-A2, -A6 (ZF LifeguardFluid 6 Plus)
VW G 060 162 (ZF LifeguardFluid 8)
ZF 6-speed, 8-speed & 9-speed transmissions
Service-fill for 8 and 9 speed step-ATs

eMobility Claims

BYD Dedicated Hybrid Transmission (DHT)
Ford Escape Hybrid eCVT
Honda e:HEV
Honda iMMD
Hyundai ATF-I2
Jatco JR712E
Mazda SKYACTIVE-HYBRID
Nissan Altima Hybrid
Toyota THSII/Toyota Prius
Toyota e-Transaxle Fluid TE for THS 5th Gen. / Toyota Noah, Voxy etc.
ZF LifeGuard Hybrid 1 (ZF No. AA02.836.455)
ZF LifeGuard Hybrid 2 (ZF No. 0671.090.548)
ZF LifeGuard Hybrid 4 (ZF No. 5961.308.625)

